

Technical data sheet LIPAREMOVE BLUE

General

Description	Solvent based paint remover – methylene chloride free
Properties	<ul style="list-style-type: none"> Removes graffiti without attacking the underlying protective anti-graffiti protective layer Non corrosive for masonry Light gel structure enabling as well spray as brush application Flammable
Use	<ul style="list-style-type: none"> Removal of graffiti on Lipaprotect AG15 anti-graffiti varnish

Technical data

Viscosity	Light thixotropic gel
Color	Colorless
Density	0,95-1,00 g/cm ³ bij 20 °C
Solids content	6%

Application information

Application tools	Brush or spray
Application conditions	<ul style="list-style-type: none"> Apply Liparemove blue onto the surface and allow to act for 5-10' Remove afterwards with clothes, scrubbing brush , limited/high pressure water cleaning Repeat if necessary Rinse with water
Consumption	1-3 m ² /L depending on layer thickness or paint type
Temperature	Preferably apply at temperatures between 5°C-25°C. Do not apply in full sunlight
Equipment cleaning	Acetone or white spirit
Health & Safety info	<ul style="list-style-type: none"> Although Liparemove blue is not toxic it has strong skin absorbing properties requiring protective clothing including appropriated hand and eye protection Butyl rubber gloves are resistant to this product and recommended Liparemove blue can cause eye irritation Avoid/minimize inhaling of solvents Always work in a well ventilated area Keep away of electric sparks Consult carefully the Health & Safety datasheets prior to use

Delivery conditions

Packaging	<ul style="list-style-type: none">• 5L plastic
Stability	Max 12 months in an unopened packaging protected against extreme weather conditions.